

---

## NASM21296 Series

---

### Flanged Head, Steel, External Wrenching, Tension Bolts

MS21296-03002	thru	MS21296-03064	(.1900-32 diameter)
MS21296-04002	thru	MS21296-04096	(.2500-28 diameter)
MS21296-05002	thru	MS21296-05096	(.3125-24 diameter)
MS21296-06002	thru	MS21296-06096	(.3750-24 diameter)
MS21296-07005	thru	MS21296-07096	(.4375-20 diameter)
MS21296-08006	thru	MS21296-08096	(.5000-20 diameter)
MS21296-09007	thru	MS21296-09096	(.5625-18 diameter)
MS21296-10008	thru	MS21296-10112	(.6250-18 diameter)
MS21296-12010	thru	MS21296-12112	(.7500-16 diameter)
MS21296-14012	thru	MS21296-14112	(.8750-14 diameter)
MS21296-16014	thru	MS21296-16112	(1.0000-12 diameter)

---

**Material:**

Alloy Steel – H-11

**Material Spec:**

AMS6487

**Tensile Strength:**

260 KSI Min.

**Hardness:**

51-54 HRC

**Finish:**

Cadmium Coated (Vaccum Deposited) per AMS-C-8837, TYPE 2, CLASS 2

**Drilling Options:**

No Hole

example: MS21296-04008

Drill Head for Safety Wire – add “H” (replace hyphen)

example: MS21296H04008

**Thread Length:**

Available in the entire range of standard lengths

*For inquiries or to place an order please call us at 718-847-6321.*