
NAS1003 thru NAS1020 Series

Hex Head, Stainless Steel, High Precision Aerospace Bolts

NAS1003-1	thru	NAS1003-100	(.1900-32 diameter)
NAS1004-1	thru	NAS1004-100	(.2500-28 diameter)
NAS1005-1	thru	NAS1005-100	(.3125-24 diameter)
NAS1006-1	thru	NAS1006-100	(.3750-24 diameter)
NAS1007-1	thru	NAS1007-100	(.4375-20 diameter)
NAS1008-1	thru	NAS1008-100	(.5000-20 diameter)
NAS1009-1	thru	NAS1009-100	(.5625-18 diameter)
NAS1010-1	thru	NAS1010-100	(.6250-18 diameter)
NAS1012-1	thru	NAS1012-100	(.7500-16 diameter)
NAS1014-1	thru	NAS1014-100	(.8750-14 diameter)
NAS1016-1	thru	NAS1016-100	(1.0000-14 diameter)
NAS1018-1	thru	NAS1018-100	(1.1250-12 diameter)
NAS1020-1	thru	NAS1020-100	(1.2500-12 diameter)

Material:

Stainless Steel – A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

140,000 PSI Min.

Hardness:

24-35 HRC

Finish:

Passivated per QQ-P-35 or AMS2700

Heat Treatment Spec:

AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

Drill Shank for Cotter Pin

example: NAS1003-1

No Hole – add “A” suffix

example: NAS1003-1A

Drill 3 Holes through Head for Safety Wire – add “H” suffix

example: NAS1003-1H

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414