
NAS1102E Series

Flat 100 Degree Head, Alloy Steel, Machine Screws

| | | | |
|---------------|------|----------------|---------------------|
| NAS1102E02-10 | thru | NAS1102E02-100 | (.0860-56 diameter) |
| NAS1102E04-10 | thru | NAS1102E04-100 | (.1120-40 diameter) |
| NAS1102E06-10 | thru | NAS1102E06-100 | (.1380-32 diameter) |
| NAS1102E08-10 | thru | NAS1102E08-100 | (.1640-32 diameter) |
| NAS1102E3-10 | thru | NAS1102E3-100 | (.1900-32 diameter) |
| NAS1102E4-10 | thru | NAS1102E4-100 | (.2500-28 diameter) |
| NAS1102E5-10 | thru | NAS1102E5-100 | (.3125-24 diameter) |
| NAS1102E6-10 | thru | NAS1102E6-100 | (.3750-24 diameter) |

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5737

Tensile Strength:

160 KSI Min.

Finish Options:

Clean and Passivate per QQ-P-35

example: NAS1102E02-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS1102E02H10DP

Thread:

Full Thread

Drive Recess:

Offset Cruciform Recess

For inquiries or to place an order please call us at 718-847-6321.