
NAS1102 Series

Flat 100 Degree Head, Alloy Steel, Machine Screws

NAS1102-02-10	thru	NAS1102-02-100	(.0860-56 diameter)
NAS1102-04-10	thru	NAS1102-04-100	(.1120-40 diameter)
NAS1102-06-10	thru	NAS1102-06-100	(.1380-32 diameter)
NAS1102-08-10	thru	NAS1102-08-100	(.1640-32 diameter)
NAS1102-3-10	thru	NAS1102-3-100	(.1900-32 diameter)
NAS1102-4-10	thru	NAS1102-4-100	(.2500-28 diameter)
NAS1102-5-10	thru	NAS1102-5-100	(.3125-24 diameter)
NAS1101-6-10	thru	NAS1102-6-100	(.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1102-02-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 with Dull Black Chromate Finish

– add “**B**” suffix example: NAS1102-02-10B

Heat Treatment Spec:

AMS-H-6875

Thread:

Full Thread

Drive Recess:

Offset Cruciform Recess

For inquiries or to place an order please call us at 718-847-6321.