

---

## NAS1151 thru NAS1158 Series

---

### Flat 100 Degree Flush Tension Head, Alloy Steel, Precision Aerospace Screw

NAS1151-1	thru	NAS1151-96	(.1380-32 diameter)
NAS1152-2	thru	NAS1152-96	(.1640-32 diameter)
NAS1153-2	thru	NAS1153-96	(.1900-32 diameter)
NAS1154-2	thru	NAS1154-96	(.2500-28 diameter)
NAS1155-3	thru	NAS1155-96	(.3125-24 diameter)
NAS1156-4	thru	NAS1156-96	(.3750-24 diameter)
NAS1157-4	thru	NAS1157-96	(.4375-20 diameter)
NAS1158-5	thru	NAS1158-96	(.5000-20 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 8740

**Material Spec:**

MIL-S-5626, MIL-S-8844, MIL-S-6049

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1151-1

Drill Shank for Cotter Pin – add “D” (replace hyphen)

example: NAS1151-1D

**Drive Option:**

Offset Cruciform Recess– add “R” suffix

example: NAS1151-1DR

*For inquiries or to place an order please call us at 718-847-6321.*