

NAS1161 thru NAS1168 Series

Self-Locking, Flat 100 Degree Head, Alloy Steel, Shear Screws

NAS1161-10	thru	NAS1161-100	(.1380-32 diameter)
NAS1162-10	thru	NAS1162-100	(.1640-32 diameter)
NAS1163-10	thru	NAS1163-100	(.1900-32 diameter)
NAS1164-10	thru	NAS1164-100	(.2500-28 diameter)
NAS1165-10	thru	NAS1165-100	(.3125-24 diameter)
NAS1166-10	thru	NAS1166-100	(.3750-24 diameter)
NAS1167-10	thru	NAS1167-100	(.4375-20 diameter)
NAS1168-10	thru	NAS1168-100	(.5000-20 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6382, AMS6415, AMS6484, AMS6327, AMS6322, AMS6325

Tensile Strength:

160-180 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

example: NAS1161-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2, with Dull Black Chromate Treatment

– add “C” suffix example: NAS1161-10C

Heat Treatment Spec:

AMS2759

Thread:

Short Thread

Locking Element Options:

None

example: NAS1161-10

Nylon Strip Type Locking Element – add “L” (suffix)

example: NAS1161-10L

Nylon Pellet Type Locking Element – add “N” (suffix)

example: NAS1161-10N

Nylon Patch Type Locking Element – add “B” (suffix)

example: NAS1161-10B

PCTFE Strip Type Locking Element – add “LK” (suffix)

example: NAS1161-10LK

PCTFE Pellet Type Locking Element – add “NK” (suffix)

example: NAS1161-10NK

PCTFE Optional Locking Element (Applicable for One Torque Cycle) – add “K” (suffix)

example: NAS1161-10K

Polyester Patch Type Locking Element – add “J” (suffix)

example: NAS1161-10J

Recess:

Offset Crusiform Recess

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414