

---

## NAS1190 Series

---

### Pan Head, Alloy Steel, Full Thread, Self-Locking Screw

NAS1190-02-3	thru	NAS1190-02-96	(.0860-56 diameter)
NAS1190-04-3	thru	NAS1190-04-96	(.1120-40 diameter)
NAS1190-06-3	thru	NAS1190-06-96	(.1380-32 diameter)
NAS1190-08-3	thru	NAS1190-08-96	(.1640-32 diameter)
NAS1190-3-3	thru	NAS1190-3-96	(.1900-32 diameter)
NAS1190-4-3	thru	NAS1190-4-96	(.2500-28 diameter)
NAS1190-5-3	thru	NAS1190-5-96	(.3125-24 diameter)
NAS1190-6-3	thru	NAS1190-6-96	(.3750-24 diameter)

---

#### Material:

Alloy Steel – 4140, 4340, E4340, 8740

#### Material Spec:

AMS6382, AMS6484, AMS6415, AMS6322, MIL-S-6049

#### Tensile Strength:

160-180 KSI Min.

#### Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

#### Heat Treatment Spec:

AMS-H-6875

#### Thread:

Full Thread

#### Locking Element:

Nylon Strip Type Locking Element – add “**L**” suffix  
example: NAS1190-4-3L

Nylon Pellet Type Locking Element – add “**N**” suffix  
example: NAS1190-4-3N

Nylon Patch Type Locking Element – add “**B**” suffix  
example: NAS1190-4-3B

PCTFE Strip Type Locking Element – add “**F**” suffix  
example: NAS1190-4-3F

PCTFE Pellet Type Locking Element – add “**G**” suffix  
example: NAS1190-4-3G

PCTFE Pellet Type with optional Locking Element – add “**K**” suffix  
example: NAS1190-4-3K

Polyethylene Patch Type Locking Element – add “**J**” suffix  
example: NAS1190-4-3J

#### Drive Resess:

Cruciform Recess per NASM9006 – add “**P**” after first dash number  
example: NAS1190-4P3

Offset Cruciform Recess per NASM14191 – add “**R**” after first dash number  
example: NAS1190-4R3

Offset Cruciform Recess per NASM33781 – add “**T**” after first dash number  
example: NAS1190-4T3

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414