
NAS1191 Series

Flat Fillister Head, Alloy Steel, Full Thread, Self-Locking Screw

NAS1191-02-3	thru	NAS1191-02-96	(.0860-56 diameter)
NAS1191-04-3	thru	NAS1191-04-96	(.1120-40 diameter)
NAS1191-06-3	thru	NAS1191-06-96	(.1380-32 diameter)
NAS1191-08-3	thru	NAS1191-08-96	(.1640-32 diameter)
NAS1191-3-3	thru	NAS1191-3-96	(.1900-32 diameter)
NAS1191-4-3	thru	NAS1191-4-96	(.2500-28 diameter)
NAS1191-5-3	thru	NAS1191-5-96	(.3125-24 diameter)
NAS1191-6-3	thru	NAS1191-6-96	(.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, E4340, 8740

Material Spec:

AMS6382, AMS6484, AMS6415, AMS6322, AMS6325, AMS6327

Tensile Strength:

160-180 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2
example: NAS1191-4-3

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 with Dull Black Chromate Finish
– add “A” suffix example: NAS1191-4-3A

Heat Treatment Spec:

AMS2759

Thread:

Full Thread

Locking Element:

Nylon Strip Type Locking Element – add “L” suffix
example: NAS1191-5T10L

Nylon Pellet Type Locking Element – add “N” suffix
example: NAS1191-5T10N

Nylon Patch Type Locking Element – add “B” suffix
example: NAS1191-5T10B

PCTFE Strip Type Locking Element – add “LK” suffix
example: NAS1191-5T10LK

PCTFE Pellet Type Locking Element – add “NK” suffix
example: NAS1191-5T10NK

PCTFE Pellet Type with Optional Element (for one torque cycle) – add “K” suffix
example: NAS1191-5T10K

Polyethylene Patch Type Locking Element – add “J” suffix
example: NAS1191-5T10J

Drive Resess:

Cruciform Recess – add “P” (replace second hyphen)
example: NAS1191-4P10

Offset Cruciform – add “T” (replace second hyphen)
example: NAS1191E4T10

For inquiries or to place an order please call us at 718-847-6321.