

---

## NAS1191E Series

---

### Flat Fillister Head, CRES, Full Thread, Self-Locking Screw

NAS1191E02-3	thru	NAS1191E02-96	(.0860-56 diameter)
NAS1191E04-3	thru	NAS1191E04-96	(.1120-40 diameter)
NAS1191E06-3	thru	NAS1191E06-96	(.1380-32 diameter)
NAS1191E08-3	thru	NAS1191E08-96	(.1640-32 diameter)
NAS1191E3-3	thru	NAS1191E3-96	(.1900-32 diameter)
NAS1191E4-3	thru	NAS1191E4-96	(.2500-28 diameter)
NAS1191E5-3	thru	NAS1191E5-96	(.3125-24 diameter)
NAS1191E6-3	thru	NAS1191E6-96	(.3750-24 diameter)

---

**Material:**

CRES – A286

**Material Spec:**

AMS5731, AMS5732, AMS5737

**Tensile Strength:**

160-190 KSI Min.

**Finish Options:**

Clean and Passivate per AMS2700, METHOD 1, CLASS 4  
example: NAS1191E3-3

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “H” suffix  
example: NAS1191E5T10LKH

**Heat Treatment Spec:**

AMS2759

**Thread:**

Full Thread

**Locking Element:**

Nylon Strip Type Locking Element – add “L” suffix  
example: NAS1191E5T10L

Nylon Pellet Type Locking Element – add “N” suffix  
example: NAS1191E5T10N

Nylon Patch Type Locking Element – add “B” suffix  
example: NAS1191E5T10B

PCTFE Strip Type Locking Element – add “LK” suffix  
example: NAS1191E5T10LK

PCTFE Pellet Type Locking Element – add “NK” suffix  
example: NAS1191E5T10NK

PCTFE Pellet Type with Optional Element (for one torque cycle) – add “K” suffix  
example: NAS1191E5T10K

Polyethylene Patch Type Locking Element – add “J” suffix  
example: NAS1191E5T10J

**Drive Resess:**

Cruciform Recess – add “P” (replace second hyphen)  
example: NAS1191E4P10

Offset Cruciform – add “T” (replace second hyphen)  
example: NAS1191E4T10

*For inquiries or to place an order please call us at 718-847-6321.*