

---

## NAS1202 thru NAS1210 Series

---

### Hex Head, Alloy Steel, High Precision Aerospace Bolts

NAS1202-1	thru	NAS1202-96	(.1640-32 diameter)
NAS1203-1	thru	NAS1203-96	(.1900-32 diameter)
NAS1204-1	thru	NAS1204-96	(.2500-28 diameter)
NAS1205-1	thru	NAS1205-96	(.3125-24 diameter)
NAS1206-1	thru	NAS1206-96	(.3750-24 diameter)
NAS1207-1	thru	NAS1207-96	(.4375-20 diameter)
NAS1208-4	thru	NAS1208-96	(.5000-20 diameter)
NAS1209-5	thru	NAS1209-96	(.5625-18 diameter)
NAS1210-5	thru	NAS1210-96	(.6250-18 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 8740

**Material Spec:**

AMS5853

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish Options:**

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 2 – add “W” suffix  
example: NAS1202-1W

**Heat Treatment Spec:**

MIL-H-6875, AMS-H-6875, AS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1202-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1202-1D

*For inquiries or to place an order please call us at 718-847-6321.*