
NAS1218 Series

Pan Head, Stainless Steel, High Precision Aerospace Machine Bolts

NAS1218-04CR1	thru	NAS1218-04CR100	(.1120-40 diameter)
NAS1218-06CR1	thru	NAS1218-06CR100	(.1380-32 diameter)
NAS1218-08CR1	thru	NAS1218-08CR100	(.1640-32 diameter)
NAS1218-3CR1	thru	NAS1218-3CR100	(.1900-32 diameter)
NAS1218-4CR1	thru	NAS1218-4CR100	(.2500-28 diameter)
NAS1218-5CR1	thru	NAS1218-5CR100	(.3125-24 diameter)
NAS1218-6CR1	thru	NAS1218-6CR100	(.3750-24 diameter)

Material:

Stainless Steel – CRES 302 or 305

Material Spec:

QQ-S-763

Tensile Strength:

125 KSI Min.

Finish:

Passivated per QQ-P-35

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Self-Locking Options:

None

example: NAS1218-04CR1

Self-Locking Element – add “L” add suffix

example: NAS1218-04CR1L

Recess Options:

Dovetail Slot Recess

example: NAS1218-04CR1

Offset Cruciform Recess – add “R” (replace hyphen)

example: NAS1218R04CR1

For inquiries or to place an order please call us at 718-847-6321.