
NAS1298 Series

Brazier Head, Alloy Steel, High Precision Shoulder Machine Screw

NAS1298-06-1 thru NAS1298-06-8 (.1380-32 diameter)
NAS1298-3-1 thru NAS1298-3-11 (.1900-32 diameter)
NAS1298-4-2 thru NAS1298-4-13 (.2500-28 diameter)
NAS1298-5-2 thru NAS1298-5-15 (.3125-24 diameter)
NAS1298-6-3 thru NAS1298-6-18 (.3750-24 diameter)
NAS1298-7-3 thru NAS1298-7-22 (.4375-20 diameter)

Material:

Alloy Steel – Low Carbon Material Steel conforming to material spec

Material Spec:

AMS6300, MIL-S-6049, MIL-S-6050, MIL-S-6098, MIL-S-6758

Tensile Strength:

125-145 KSI Min.

Hardness:

26-32 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1298-06-1

Drill Shank for Cotter Pin – add “D” (replace hyphen)

example: NAS1298-06D1

For inquiries or to place an order please call us at 718-847-6321.