
NAS1352 Series

Socket Head Cap, Alloy Steel, High Precision Aerospace Screws

NAS1352-4-1	thru	NAS1352-4-100	(.2500-20 diameter)
NAS1352-5-1	thru	NAS1352-5-100	(.3125-18 diameter)
NAS1352-6-1	thru	NAS1352-6-100	(.3750-16 diameter)
NAS1352-7-1	thru	NAS1352-7-100	(.4375-14 diameter)
NAS1352-8-1	thru	NAS1352-8-100	(.5000-13 diameter)
NAS1352-10-1	thru	NAS1352-10-100	(.6250-11 diameter)
NAS1352-12-1	thru	NAS1352-12-100	(.7500-10 diameter)
NAS1352-14-1	thru	NAS1352-14-100	(.8750-9 diameter)
NAS1352-16-1	thru	NAS1352-16-100	(1.0000-8 diameter)
NAS1352-20-1	thru	NAS1352-20-100	(1.2500-7 diameter)
NAS1352-24-1	thru	NAS1352-24-100	(1.5000-6 diameter)

Material:

Alloy Steel – 8740

Material Spec:

AMS6322

Tensile Strength:

170-180 KSI Min.

Hardness:

37-45 HRC

Finish:

Black Oxide in Accordance with MIL-DTL-13924, CLASS 1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix
example: NAS1351-4-1P

Heat Treatment Spec:

MIL-H-6875 AMS-H-6875, AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1352-4-1

Drill 6 Holes in Head Spaced 60 Degrees Apart – add “H” (replace hyphen)

example: NAS1352-4H1

Locking Options:

None

example: NAS1352-4-1

Optional Type Locking Element – add “LE” (replace hyphen)

example: NAS1352-4LE1

Longitudinal Strip Locking Element – add “LL” (replace hyphen)

example: NAS1352-4LL1

Pellet Locking Element – add “LN” (replace hyphen)

example: NAS1352-4LN1

Patch Type Locking Element – add “LB” (replace hyphen)

example: NAS1352-4LB1

For inquiries or to place an order please call us at 718-847-6321.