

---

## NAS1578A Series

---

### Flat Pan Head, Alloy Steel, High Precision Aerospace Bolts

NAS1578A3-2	thru	NAS1578A3-96	(.1900-32 diameter)
NAS1578A4-2	thru	NAS1578A4-96	(.2500-28 diameter)
NAS1578A5-4	thru	NAS1578A5-96	(.3125-24 diameter)
NAS1578A6-4	thru	NAS1578A6-96	(.3750-24 diameter)
NAS1578A7-4	thru	NAS1578A7-96	(.4375-20 diameter)
NAS1578A8-4	thru	NAS1578A8-96	(.5000-20 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 6150, 8735, 8740

**Material Spec:**

MIL-S-5626, AMS6415, MIL-S-5000, MIL-S-6049

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Drive Options:**

None

example: NAS1578A3-1

Slotted Dovetail Recess – add “**H**” (replace hyphen)

example: NAS1578A3H1

Offset Cruciform Recess – add “**R**” (replace hyphen)

example: NAS1578A3R1

**Self-Locking Options:**

None

example: NAS1578A3H1

Self-Locking Element – add “**L**” add suffix

example: NAS1578A3H1L

*For inquiries or to place an order please call us at 718-847-6321.*