

---

## NAS1801 Series

---

### Hex Head with Cruciform Recess, Alloy Steel, High Precision Screw

NAS1801-04-1 thru NAS1801-04-100 (.1120-40 diameter)  
NAS1801-06-1 thru NAS1801-06-100 (.1380-32 diameter)  
NAS1801-08-1 thru NAS1801-08-100 (.1640-32 diameter)  
NAS1801-3-1 thru NAS1801-3-100 (.1900-32 diameter)  
NAS1801-4-1 thru NAS1801-4-100 (.2500-28 diameter)  
NAS1801-5-1 thru NAS1801-5-100 (.3125-24 diameter)  
NAS1801-6-1 thru NAS1801-6-100 (.3750-24 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 8740

**Material Spec:**

AMS6322, AMS6325, AMS6327, AMS6382, AMS6415, AMS6484

**Tensile Strength:**

160-180 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1801-04-1

Drilled Head for Safety Wire – add “D” (replace hyphen)

example: NAS1801-3D1 thru NAS1801-6D100

*For inquiries or to place an order please call us at 718-847-6321.*