
NAS1972 thru NAS1980 Series

100 Degree Flush Head, Alloy Steel, High Precision Aerospace Bolts

NAS1972-1	thru	NAS1972-100	(.1640-32 diameter)
NAS1973-1	thru	NAS1973-100	(.1900-32 diameter)
NAS1974-1	thru	NAS1974-100	(.2500-28 diameter)
NAS1975-1	thru	NAS1975-100	(.3125-24 diameter)
NAS1976-1	thru	NAS1976-100	(.3750-24 diameter)
NAS1977-1	thru	NAS1977-100	(.4375-20 diameter)
NAS1978-1	thru	NAS1978-100	(.5000-20 diameter)
NAS1979-1	thru	NAS1979-100	(.5625-18 diameter)
NAS1980-1	thru	NAS1980-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6322, AMS6382, AMS6484, MIL-S-6049

Tensile Strength:

180-200 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS-H-81200

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1972-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1972-1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS1972-1H

Offset Cruciform Recess – add “T” suffix

example: NAS1972-1T

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS1972-1X

.0312 Oversize – add “Y” suffix

example: NAS1972-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414