

---

## NAS2803 thru NAS2810 Series

---

### 100 Degree Head, Alloy Steel, High Precision Aerospace Bolts

NAS2803-2	thru	NAS2803-96	(.1900-32 diameter)
NAS2804-3	thru	NAS2804-96	(.2500-28 diameter)
NAS2805-3	thru	NAS2805-96	(.3125-24 diameter)
NAS2806-3	thru	NAS2806-96	(.3750-24 diameter)
NAS2807-5	thru	NAS2807-96	(.4375-20 diameter)
NAS2808-5	thru	NAS2808-96	(.5000-20 diameter)
NAS2809-5	thru	NAS2809-96	(.5625-18 diameter)
NAS2810-5	thru	NAS2810-96	(.6250-18 diameter)

---

**Material:**

Alloy Steel – 4140, 4340, 8740

**Material Spec:**

MIL-S-5000, MIL-S-5626, MIL-S-6049

**Tensile Strength:**

180-200 KSI

**Hardness:**

36-40 HRC

**Finish:**

Cadmium Plated per NAS672

**Heat Treatment Spec:**

MIL-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Drive:**

Offset Cruciform Recess

*For inquiries or to place an order please call us at 718-847-6321.*