
NAS2832 thru NAS2840 Series

100 Degree Flat Head, Alloy Steel, High Precision Aerospace Bolts

NAS2832-2	thru	NAS2832-96	(.1640-32 diameter)
NAS2833-2	thru	NAS2833-96	(.1900-32 diameter)
NAS2834-3	thru	NAS2834-96	(.2500-28 diameter)
NAS2835-3	thru	NAS2835-96	(.3125-24 diameter)
NAS2836-3	thru	NAS2836-96	(.3750-24 diameter)
NAS2837-4	thru	NAS2837-96	(.4375-20 diameter)
NAS2838-4	thru	NAS2838-96	(.5000-20 diameter)
NAS2839-5	thru	NAS2839-96	(.5625-18 diameter)
NAS2840-5	thru	NAS2840-96	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

180-200 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2832-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS2832-1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2832-1H

Offset Cruciform Recess – add “T” suffix

example: NAS2832-1T

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2832-1X

.0312 Oversize – add “Y” suffix

example: NAS2832-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414