

---

## NAS4450H Series

---

### Protruding Shear Head, Alloy Steel, Crimp Pin

NAS4450H05-01	thru	NAS4450H05-20	(.1640-32 diameter)
NAS4450H06-01	thru	NAS4450H06-24	(.1900-32 diameter)
NAS4450H08-01	thru	NAS4450H08-28	(.2500-28 diameter)
NAS4450H10-02	thru	NAS4450H10-30	(.3125-24 diameter)
NAS4450H12-02	thru	NAS4450H12-32	(.3750-24 diameter)

---

#### Material:

Alloy Steel – H-11 Alloy Steel

#### Material Spec:

UNS T20811

#### Tensile Strength:

156 KSI Min.

#### Finish Options:

Nickel-Cadmium Plate per AMS2416

example: NAS4450H05-10

Diffused Nickel-Cadmium Plate (for high strength and/or temps. over 450 degrees F)

– add “N” (replace hyphen) example: NAS4450H05N10

#### Lubrication Options:

None

example: NAS4450H05-10

Dry Film Lubricant per AS5272, TYPE 1 or Molybdenum Disulfide per AMS-M-7866

– add “E” suffix example: NAS4450H05-10E

Chlorine-free Cetyl Alcohol per AS18732, TYPE 1, GRADE B

– add “P” suffix example: NAS4450H05-10P

#### Oversize Option:

Optional Oversize Shank Diameter – add “R” suffix

example: 4450H05-10R

*For inquiries or to place an order please call us at 718-847-6321.*