

---

## NAS5311E Series

---

### Flat Fillister Head, Alloy Steel, High Precision Aerospace Screws

NAS1219E02-1	thru	NAS1219E02-100	(.0860-56 diameter)
NAS1219E04-1	thru	NAS1219E04-100	(.1120-40 diameter)
NAS1219E06-1	thru	NAS1219E06-100	(.1380-32 diameter)
NAS1219E08-1	thru	NAS1219E08-100	(.1640-32 diameter)
NAS1219E3-1	thru	NAS1219E3-100	(.1900-32 diameter)
NAS1219E4-1	thru	NAS1219E4-100	(.2500-28 diameter)
NAS1219E5-1	thru	NAS1219E5-100	(.3125-24 diameter)
NAS1219E6-1	thru	NAS1219E6-100	(.3750-24 diameter)

---

**Material:**

CRES – A286

**Material Spec:**

AMS5731, AMS5732, AMS5737

**Tensile Strength:**

160-190 KSI Min.

**Finish Options:**

Passivated per AMS2700, METHOD 1, CLASS 4

example: NAS5311E3-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix

example: NAS5311E3P10

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Full Thread

**Drilling Options:**

No Hole

example: NAS5311E3-15

Drill Head for Safety Wire – add “H” suffix

example: NAS5311E3-15H

**Self-Locking Options:**

None

example: NAS5311E04-1

Patch Type Locking Element – add “J” add suffix

example: NAS5311E04-1J

**Recess:**

Six Lobe Recess

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414