
NAS5317E Series

Pan Head, CRES, Full Thread, Aerospace Screw

NAS5317E02-1	thru	NAS5317E02-100	(.0860-56 diameter)
NAS5317E04-1	thru	NAS5317E04-100	(.1120-40 diameter)
NAS5317E06-1	thru	NAS5317E06-100	(.1380-32 diameter)
NAS5317E08-1	thru	NAS5317E08-100	(.1640-32 diameter)
NAS5317E3-1	thru	NAS5317E3-100	(.1900-32 diameter)
NAS5317E4-1	thru	NAS5317E4-100	(.2500-28 diameter)
NAS5317E5-1	thru	NAS5317E5-100	(.3125-24 diameter)
NAS5317E6-1	thru	NAS5317E6-100	(.3750-24 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

160-190 KSI Min.

Finish:

Passivated per AMS2700, METHOD 1, CLASS 1

example: NAS5317E3-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” (replace hyphen)

example: NAS5317E3P10

Heat Treatment Spec:

AMS2759

Thread Length:

Full Thread

Self-Locking Options:

None

example: NAS5317E3-1

Patch Type Locking Element – add “J” add suffix

example: NAS5317E5P15J

Drive Resess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.