

---

## NAS5318E Series

---

### Flat Pan Head, Alloy Steel, Close Tolerance, Long Thread, Shear Bolts

NAS5318E3-1 thru NAS5318E3-96 (.1900-32 diameter)  
NAS5318E4-1 thru NAS5318E4-96 (.2500-28 diameter)  
NAS5318E5-1 thru NAS5318E5-96 (.3125-24 diameter)  
NAS5318E6-4 thru NAS5318E6-96 (.3750-24 diameter)  
NAS5318E7-4 thru NAS5318E7-96 (.4375-20 diameter)  
NAS5318E8-4 thru NAS5318E8-96 (.5000-20 diameter)

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

AMS5731, AMS5732, AMS5737, AMS5853

**Tensile Strength:**

160-190 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

Passivated per AMS2700, METHOD 1, CLASS 4

example: NAS5318E3-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” (replace hyphen)

example: NAS5318E3P1

**Heat Treatment Spec:**

AMS2759

**Thread Length:**

Available in the entire range of standard lengths

**Drive Resess:**

Six Lobe Recess

**Self-Locking Options:**

None

example: NAS5318E3-1

Self-Locking Element – add “J” add suffix

example: NAS5318E3-1J

*For inquiries or to place an order please call us at 718-847-6321.*