
NAS600 thru NAS606 Series

Pan Head, Full Thread, Alloy Steel, Aerospace Machine Screw

NAS600-1	thru	NAS600-100	(.1120-40 diameter)
NAS601-1	thru	NAS601-100	(.1380-32 diameter)
NAS602-1	thru	NAS602-100	(.1640-32 diameter)
NAS603-1	thru	NAS603-100	(.1900-32 diameter)
NAS604-1	thru	NAS604-100	(.2500-28 diameter)
NAS605-1	thru	NAS605-100	(.3125-24 diameter)
NAS606-1	thru	NAS606-100	(.3750-24 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5626, AMS6415, MIL-S-5000, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 1

example: NAS600-6

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 with Dull Black Chromate Treatment

– add “**B**” suffix example: NAS600-6B

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “**P**” suffix

example: NAS600-6P

Heat Treatment Spec:

MIL-H-6875

Drive Resess:

Cruciform Recess

For inquiries or to place an order please call us at 718-847-6321.