
NAS673 thru NAS678 Series

Hex Head, Titanium, Precision Aerospace Machine Bolts

NAS673-1	thru	NAS673-100	(.1900-32 diameter)
NAS674-1	thru	NAS674-100	(.2500-28 diameter)
NAS675-1	thru	NAS675-100	(.3125-24 diameter)
NAS676-1	thru	NAS676-100	(.3750-24 diameter)
NAS677-1	thru	NAS677-100	(.4375-20 diameter)
NAS678-1	thru	NAS678-100	(.5000-20 diameter)

Material:

Titanium – 6AL-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish:

No Finish (Clean and Degrease)

Heat Treatment Spec:

AMS2801

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS673-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS673-1D

Drill 3 Holes through Head for Safety Wire – add “H” suffix

example: NAS673-1H

Drill 3 Holes through Head for Safety Wire and Drilled Shank for Cotter Pin

– add “DH” suffix example: NAS673-1DH

For inquiries or to place an order please call us at 718-847-6321.