
NAS7600 thru NAS7616 Series

100 Degree Head, Titanium, High Precision Aerospace Bolts

NAS7600-1	thru	NAS7600-100	(.1120-40 diameter)
NAS7601-2	thru	NAS7601-100	(.1380-32 diameter)
NAS7602-2	thru	NAS7602-100	(.1640-32 diameter)
NAS7603-2	thru	NAS7603-100	(.1900-32 diameter)
NAS7604-3	thru	NAS7604-100	(.2500-28 diameter)
NAS7605-3	thru	NAS7605-100	(.3125-24 diameter)
NAS7606-3	thru	NAS7606-100	(.3750-24 diameter)
NAS7607-4	thru	NAS7607-100	(.4375-20 diameter)
NAS7608-4	thru	NAS7608-100	(.5000-20 diameter)
NAS7609-5	thru	NAS7609-100	(.5625-18 diameter)
NAS7610-5	thru	NAS7610-100	(.6250-18 diameter)
NAS7612-6	thru	NAS7612-100	(.7500-16 diameter)
NAS7614-7	thru	NAS7614-100	(.8750-14 diameter)
NAS7616-8	thru	NAS7616-100	(1.0000-12 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

Aluminum Coated per NAS4006 – add “A” (replace hyphen)

example: NAS7600A1

No Finish (Clean and Degrease) – add “U” (replace hyphen)

example: NAS7600U1

Heat Treatment Spec:

AMS-H-81200. AMS2801

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS7600A1

Drill Shank for Cotter Pin – add “D” (replace hyphen)

example: NAS7600AD1

Locking Options:

None

example: NAS7600A1

Optional Locking Element – add “L” (replace hyphen)

example: NAS7600AL1

Patch Type Locking Element – add “P” (replace hyphen)

example: NAS7600AP1

Drive Recess:

Cruciform Recess

Shank Options:

None

example: NAS7600A1

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414