
NASM24677 Series

Socket Hex Head, Alloy Steel, Cap, Drilled, Screw

MS24677-1	thru	MS24677-4	(.1120-40 diameter)
MS24677-6	thru	MS24677-12	(.1380-32 diameter)
MS24677-13	thru	MS24677-21	(.1640-32 diameter)
MS24677-22	thru	MS24677-31	(.1900-24 diameter)
MS24677-32	thru	MS24677-45	(.2500-20 diameter)
MS24677-46	thru	MS24677-61	(.3125-18 diameter)
MS24677-62	thru	MS24677-79	(.3750-16 diameter)
MS24677-80	thru	MS24677-95	(.4375-14 diameter)
MS24677-96	thru	MS24677-115	(.5000-13 diameter)
MS24677-116	thru	MS24677-131	(.6250-11 diameter)
MS24677-132	thru	MS24677-146	(.7500-10 diameter)
MS24677-147	thru	MS24677-158	(.8750-9 diameter)
MS24677-159	thru	MS24677-170	(1.0000-8 diameter)

Material:

Alloy Steel

Material Spec:

In accordance with procurement spec

Tensile Strength:

170-180 KSI Min.

Hardness:

In accordance with procurement spec

Finish:

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 3

example: MS24677-1

Aluminum Ion Vapor Coating per MIL-DTL-83488, TYPE 2, CLASS 3

– add “**A**” suffix example: MS24677-1A

No Protective Coating or Surface Treatment – add “**U**” suffix

example: MS24677-1U

Drilling:

One Hole Through Head (for MS24677-1 through MS24677-12 only)

Three Holes Through Head (for MS24677-13 and larger)

For inquiries or to place an order please call us at 718-847-6321.